

Portal > Knowledgebase > Cloud > Cloud On-Premise: IIS Settings to improve performance

Cloud On-Premise: IIS Settings to improve performance Scott Leonard - 2022-01-12 - in Cloud

After the Cloud On-Premise software is installed successfully and you've confirmed you can log in successfully, make these changes in IIS Manager to improve performance. (Some settings may already be at the recommended value.)

- 1. Start IIS Manager (type IIS into the Windows search box to find and launch).
- 2. At the upper left, expand your computer name, then click Application Pools.
- 3. In the right pane, right-click WaspPAPI, then Advanced Settings.
- 4. Under the General section, change Start Mode from OnDemand to AlwaysRunning.
- 5. Under the Process Model section, change Idle Time-out (minutes) from 20 to 0.
- 6. Under the Recycling section, change Regular Time Interval (minutes) from 240 to 0.

(another suggested value is 1740).

7. Click OK.

Idvanced Settings ? 2				×
~	(General)			
	NET CLR Version	v4.0		
	Enable 32-Bit Applications	False		
	Managed Pipeline Mode	Integrated		
	Name	WaspPAPI		
	Oueue Length	4000		
	Start Mode	AlwaysRunning		
>	CPU			
v	Process Model			
>	Generate Process Model Event Log Ent			
	Identity	ApplicationPoolIdentity		
	Idle Time-out (minutes)	0		
	Idle Time-out Action	Terminate		
	Load User Profile	True		
	Maximum Worker Processes	2		
	Ping Enabled	True		
	Ping Maximum Response Time (secon	90		
	Ping Period (seconds)	30		
	Shutdown Time Limit (seconds)	90		
	Startup Time Limit (seconds)	90		
>	Process Orphaning			
>	Rapid-Fail Protection			
v	Recycling			
	Disable Overlapped Recycle	False		
	Disable Recycling for Configuration Cl	False		
>	Generate Recycle Event Log Entry			
	Private Memory Limit (KB)	0		
	Regular Time Interval (minutes)	0		
	Request Limit	0		
>	Specific Times	TimeSpan[] Array		
1	Virtual Memory Limit (KB)	0		
СР	U			
		ОК	Canc	el

8. Repeat Steps 3-7 for WaspPSTS and WaspPIC (if you are running InventoryCloud) or WaspPAC (for AssetCloud) application pools, with same settings.

* If you are still using v1.04.05 or older, update WaspPMVC instead of WaspPIC or WaspPAC.

- 9. At the upper left, expand Sites.
- 10. Under Sites, right-click WaspAPI, Manage Website, then Advanced Settings.
- 11. Under the General section, change Preload Enabled from False to True.
- 12. Click OK.

dv	anced Settings	?)
~	(General)	
	Application Pool	WaspPAPI
	Bindings	http:*:8081:VM-SKIRCHER-26
	ID	2
	Name	WaspAPI
	Physical Path	C:\inetpub\wwwroot\WaspAPI\
	Physical Path Credentials	
	Physical Path Credentials Logon Type	ClearText
	Preload Enabled 🛛 🔴	True
>	Behavior	
Be	havior	
		OK Cancel

13. Repeat Steps 10-12 for the WaspSTS and Wasp_IC or Wasp_AC sites, with the same setting.

* Again, if you are still running v1.04.05 or older, update WaspMVC.

14. When all 3 application pools and all 3 sites have been updated, IIS Manager can be closed.