MASIS BARCODE TECHNOLOGIES

Portal > Knowledgebase > Discontinued Products > MobileAsset > Version 7 > MobileAsset v7: editing server name/IP address in service.config for Windows Mobile/CE device

MobileAsset v7: editing server name/IP address in service.config for Windows Mobile/CE device

Scott Leonard - 2019-01-15 - in Version 7

If MobileAsset has been installed on the device, edit the device's service.config file:

- a. Connect the device to the PC.
- b. In Windows Mobile Device Center, File Management, Browse the contents of your device.
- c. Navigate to:

\Program Files\MobileAsset

- d. Find the file Service. Config (or Service) and copy it to the PC.
- e. Edit the file in Notepad or other text editor, so that it refers to the new value (e.g. 169.254.2.2) in two lines, MAServiceUrl and IpSyncServiceUrl. Your file may have more lines than what are shown here.

Old:

```
<?xml version="1.0" encoding="utf-8"?>
<MobileAssetService>
<MAServiceUrl>http://PCname:10008/WaspMobileAssetService</MAServiceUrl>
<IpSyncServiceUrl>http://PCname:10008/WaspMobileAssetService</IpSyncServiceUrl>
</MobileAssetService>
```

New:

```
<?xml version="1.0" encoding="utf-8"?>
<MobileAssetService>
<MAServiceUrl>http://169.254.2.2:10008/WaspMobileAssetService</MAServiceUrl>
<IpSyncServiceUrl>http://169.254.2.2:10008/WaspMobileAssetService</IpSyncServiceUrl>
</MobileAssetService>
```

- f. Save and close the file.
- g. Copy the file back to the mobile device, overwriting the existing file.

Related Pages

- MobileAsset v7: mobile device connection troubleshooting
- MobileAsset v7 Standard with a Windows Mobile/CE Device: Initial program installation fails, or the device won't sync over the cable.