

Portal > Knowledgebase > Discontinued Products > MobileAsset > Version 7 > MobileAsset v7: Legacy Setup for mobile devices

MobileAsset v7: Legacy Setup for mobile devices

Jason Whitmer - 2023-01-23 - in Version 7

Note: For the WPA1000, use the articles linked below in Related Content instead of this article.

If MobileAsset is unable to load on your mobile device using either of the normal methods, either through Mobility in the client program, or by browsing to the service's download page at <a href="http://<Server>:10006">http://<Server>:10006 and following the instructions to download and run the installer, we can enable a Legacy mode installation, that works more similarly to MobileAsset v6.

First, on the server, look in C:\Program Files (x86)\Wasp

Technologies\MobileAsset\PocketPC\CABs and make sure all of the files in this screenshot are in that directory:

- DevMobileAssetSSP.CAB
 InstallCabs.exe
 MobileAssetPPC.CAB
 NETCFv35.Messages.EN.cab
 NETCFv35.Messages.EN.wm.cab
 NETCFv35.ppc.armv4.cab
 NETCFv35.wce.armv4.cab
 NETCFv35.wce.armv4.cab
 Sql.ppc.wce4.armv4.CAB
 sql.wce5.armv4i.CAB
 sqlce.ppc.wce4.armv4.CAB
 sqlce.pc.wce5.armv4i.CAB
 sqlce.wce5.armv4i.CAB
 Sqlce.wce5.armv4i.CAB
- **Second**, make sure you have the correct machine name for the server, and get the server's Fully Qualified Domain Name and IP Address as well. On the mobile device, open Internet Explorer, and try connecting to the service page using all three:

http://<serverlP>:10008 http://FQDN>:10008

If it connects to the service, it will display this page:

Service

This is a Windows© Communication Foundation service.

Metadata publishing for this service is currently disabled.

If you have access to the service, you can enable metadata publishing by completing the following steps to modify your web or application configuration file:

 Create the following service behavior configuration, or add the <serviceMetadata> element to an existing service behavior configuration:

```
<behaviors>
 <serviceBehaviors>
     <behavior name="MyServiceTypeBehaviors" >
         <serviceMetadata httpGetEnabled="true" />
     </behavior>
     </serviceBehaviors>
 </behaviors>
```

Make note of which of the three works.

Third, enable the legacy mode and use it to install the program on the device:

1. Clean boot the device

2. In C:\Program Files (x86)\Wasp Technologies\MobileAsset\Services\Downloads\, edit weblink.x with Notepad. Edit the file to use <servername>, <serverlP>, or <FQDN>, whichever worked in the second step above, as http://[server]:10006/Downloads/ Example: http://192.168.1.6:10006/Downloads/

3. Use the regedit command to access the Registry and navigate to

HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Wasp Technologies\MobileAsset\Options. Right click and select New > String Value. Name it **Enable Mobile Legacy Set Up**

4. Right click Enable Mobile Legacy Set Up and click Modify, and enter Yes for the value.

5. Connect the mobile device to the pc and make sure it is recognized by Windows Mobile Device Center.

6. In MobileAsset, go to Mobility > Windows Mobile / CE Setup (Legacy). Follow the prompts on screen to load the program.

7. As the program loads on the device, make sure everything loads to the default Device option, not Flash.

8. When you open the program, enter the correct address for the Service URL matching the second step above, as Service URL: http://[server]:10008

Example: http://192.168.1.6:10008

Related Pages

- <u>MobileAsset v7: mobile device connection troubleshooting</u>
- MobileAsset v7: Manual installation of CAB files to a WPA1000 mobile device
- MobileAsset v7: How to install on the WPA1000